



## NOTES:

- ① CENTERLINE OF RAIL BLOCKING OFF OF INSIDE FRONT WALL. (MIN. 28" DIMENSION)
- ② CAR TO WALL (CTW) DIMENSION IS 4 1/2" MIN.
- ③ HOISTWAY DOORS & FRAMES MUST BE INSTALLED TO COMPLY WITH THE AUTHORITY HAVING JURISDICTION REQUIREMENTS. THESE DIMENSIONS VARY. CONSULT YOUR RESIDENTIAL ELEVATORS SALES REPRESENTATIVE FOR DETAILS PRIOR TO CONSTRUCTION.
- ④ HOISTWAY DOORS TO BE SOLID CORE (BY OTHERS.)
- ⑤ CLEAR CAB DIMENSIONS BASED ON A 3/4" FLAT WALL CAB DESIGN.
- ⑥ MIN. CLEARANCE TO ALLOW FOR MOTOR/ BRAKE/ GEARBOX

## MINIMUM RETURN REQUIREMENTS FOR GATE STACK

CAB TYPE	RAIL-SIDE RETURN	NON RAIL-SIDE RETURN
WOOD	18 1/2"	5 1/2"
STAINLESS STEEL	20"	5 1/2"

*All Traction Elevators require an access panel for emergency lowering. Access panel size and location must be discussed with your Residential Elevators Sales Representative prior to construction.*

## STANDARD HOISTWAY PLAN - RAIL SIDE GATE STACK

NOTE: NTS - ALL DIMENSIONS ARE APPROXIMATE