


CONSULT FACTORY
IF LARGER

NOTES:

- ① CENTERLINE OF RAIL BLOCKING OFF OF INSIDE FRONT WALL.
(MIN. 28" DIMENSION)
- ② CAR TO WALL (CTW) DIMENSION IS 3" MIN.
- ③ HOISTWAY DOORS & FRAMES MUST BE INSTALLED TO COMPLY
WITH THE AUTHORITY HAVING JURISDICTION REQUIREMENTS.
THESE DIMENSIONS VARY. CONSULT YOUR
RESIDENTIAL ELEVATORS SALES REPRESENTATIVE
FOR DETAILS PRIOR TO CONSTRUCTION.
- ④ HOISTWAY DOORS TO BE SOLID CORE (BY OTHERS.)
- ⑤ CLEAR CAB DIMENSIONS BASED ON A 3/4" FLAT WALL
CAB DESIGN.
- ⑥ MIN. CLEARANCE TO ALLOW FOR MOTOR/ BRAKE/ GEARBOX



MINIMUM RETURN REQUIREMENTS FOR GATE STACK

CAB TYPE	RAIL-SIDE RETURN	NON RAIL-SIDE RETURN
WOOD	18 1/2"	5 1/2"
STAINLESS STEEL	20"	5 1/2"

*All Traction Elevators require an access panel for emergency lowering.
Access panel size and location must be discussed with your
Residential Elevators Sales Representative prior to construction.*

STANDARD HOISTWAY PLAN - RAIL SIDE GATE STACK

NOTE: NTS - ALL DIMENSIONS ARE APPROXIMATE