



NOTES:

- ① IF PLATFORM SIZE IS REDUCED, THEN THE BLOCKING IS TO BE POSITIONED SUCH THAT IT IS CENTERED ON THE PLATFORM.
(PLATFORM DEPTH / 2) + 2" = CENTERLINE OF RAIL BLOCKING OFF OF INSIDE FRONT WALL. (MIN. 28" DIMENSION)
- ② CAR TO WALL (CTW) DIMENSION VARIES
- ③ **HOISTWAY DOORS & FRAMES MUST BE INSTALLED TO COMPLY WITH THE AUTHORITY HAVING JURISDICTION REQUIREMENTS. THESE DIMENSIONS VARY. CONSULT YOUR RESIDENTIAL ELEVATORS SALES REPRESENTATIVE FOR DETAILS PRIOR TO CONSTRUCTION.**
- ④ HOISTWAY DOORS TO BE SOLID CORE (BY OTHERS.)
- ⑤ CLEAR CAB DIMENSIONS BASED ON A 3/4" FLAT WALL CAB DESIGN.
- ⑥ MIN. CLEARANCE TO ALLOW FOR MOTOR/ BRAKE/ GEARBOX

HOISTWAY TOLERANCES

| | RETURN (RAIL SIDE ONLY) | WIDTH | | DEPTH | |
|--------------|----------------------------|-------|------|----------------------------------|----------------------------------|
| | | MIN. | MAX. | MIN. | MAX. |
| 12 SQFT | 12" | 56" | | 54" | |
| SINGLE ENTRY | 12" | 56" | 62" | 54" | 60" |
| PASSTHRU | 12" | 56" | 62" | 53 ¹ / ₂ " | 54 ¹ / ₂ " |

STANDARD HOISTWAY PLAN

NOTE: ALL DIMENSIONS ARE APPROXIMATE

*All Traction Elevators require an access panel for emergency lowering.
Access panel size and location must be discussed with your
Residential Elevators Sales Representative prior to construction.*