

STANDARD HOISTWAY PLAN

NOTE: NTS - ALL DIMENSIONS ARE APPROXIMATE

NOTES:

- (MIN. 28" DIMENSION)

 FOR PASS THROUGH APPLICATIONS, CENTER BLOCKING
 INSIDE HOISTWAY.
- (2) CAR TO WALL (CTW) DIMENSION IS 3" MIN.
- HOISTWAY DOORS & FRAMES MUST BE INSTALLED TO COMPLY WITH THE AUTHORITY HAVING JURISDICTION REQUIREMENTS. THESE DIMENSIONS VARY. CONSULT YOUR RESIDENTIAL ELEVATORS SALES REPRESENTATIVE FOR DETAILS PRIOR TO CONSTRUCTION.
- (4) HOISTWAY DOORS TO BE SOLID CORE (BY OTHERS.)
- 5 CLEAR CAB DIMENSIONS BASED ON A 3/4" FLAT WALL CAB DESIGN.
- (6) MIN. CLEARANCE TO ALLOW FOR MOTOR/ BRAKE/ GEARBOX

ALL TRACTION ELEVATORS REQUIRE AN ACCESS PANEL FOR EMERGENCY LOWERING. ACCESS PANEL SIZE AND LOCATION MUST BE DISCUSSED WITH YOUR RESIDENTIAL ELEVATORS SALES REPRESENTATIVE PRIOR TO CONSTRUCTION.

