

STANDARD HOISTWAY PLAN

NOTE: ALL DIMENSIONS ARE APPROXIMATE

NOTES:

- 1) MAXIMUM HOISTWAY DEPTH TO BE 54" (+/- 1/2")
- (2) CAR TO WALL (CTW) DIMENSION VARIES
- 3 HOISTWAY DOORS & FRAMES MUST BE INSTALLED TO COMPLY WITH THE AUTHORITY HAVING JURISDICTION REQUIREMENTS. THESE DIMENSIONS VARY. CONSULT YOUR RESIDENTIAL ELEVATORS SALES REPRESENTATIVE FOR DETAILS PRIOR TO CONSTRUCTION.
- (4) HOISTWAY DOORS TO BE SOLID CORE (BY OTHERS.)
- (5) CLEAR CAB DIMENSIONS BASED ON A 3/4" FLAT WALL CAB DESIGN.

HOISTWAY TOLERANCES					
	RETURN (RAIL SIDE ONLY)	WIDTH		DEPTH	
		MIN.	MAX.	MIN.	MAX.
12 SQFT	12"	56"		54"	
SINGLE ENTRY	12"	56"	62"	54"	60"
PASSTHRU	12"	56"	62"	53½"	54½"

All Traction Elevators require an access panel for emergency lowering.

Access panel size and location must be discussed with your

Residential Elevators Sales Representative prior to construction.

