

## NOTES:

- (1) MAXIMUM HOISTWAY DEPTH TO BE 60" (+/- 1/2")
- (2) CAR TO WALL (CTW) DIMENSION VARIES
- 3 HOISTWAY DOORS & FRAMES MUST BE INSTALLED TO COMPLY WITH THE AUTHORITY HAVING JURISDICTION REQUIREMENTS.
  THESE DIMENSIONS VARY. CONSULT YOUR
  RESIDENTIAL ELEVATORS SALES REPRESENTATIVE
  FOR DETAILS PRIOR TO CONSTRUCTION.
- (4) HOISTWAY DOORS TO BE SOLID CORE (BY OTHERS.)

HOISTWAY TOLERANCES					
	RETURN (RAIL SIDE ONLY)	WIDTH		DEPTH	
		MIN.	MAX.	MIN.	MAX.
15 SQFT	12"	60"		60"	
SINGLE ENTRY	12"	60"	66"	60"	66"
PASS THRU	12"	60"	66"	59½"	60 <u>1</u> "

## STANDARD HOISTWAY PLAN

NOTE: ALL DIMENSIONS ARE APPROXIMATE

All Traction Elevators require an access panel for emergency lowering.

Access panel size and location must be discussed with your

Residential Elevators Sales Representative prior to construction.

